



**CLIMATIZER
INSULATION**

ANY JOB. ANY SIZE. ANY PLACE.

60 Years of American Ingenuity

475



The **475** is an economical machine for the professional contractor or a do-it-yourself rental market. Designed for low maintenance, rugged performance, and high production. Capable of blowing all types and brands of loosefill insulation to the manufacturer's specifications.

- Adaptable fold down loading door
- Removable all steel airlock allows for quick access for maintenance
- Light weight machine
- User friendly electric dashboard
- Clear acrylic safety guard allows for easy inspection
- Durable powder coat finish
- Large 14 amp / 2 stage blower
- Semi pneumatic run flat treaded tires
- Built in tool holder

MATERIAL PRODUCTION RATE

	MATERIAL
CELLULOSE	2100 (953) * 70 Bags per hr.*
FIBERGLASS	700 (318) * 23 Bags per hr.*

w/single 14amp Blower

* lbs/hr (kg/hr) rating with 150 ft. (45.8 m.) of
3" (7.6 cm.) hose at 16 ft. (4.8 m.) elevation.

NOTE:

Manufacturer's product brand, density and variable blowing conditions will affect production rate.

Backed by a manufacturer's
2-YEAR WARRANTY - Made in the U.S.A.

CLIMATIZER INSULATION | Proud Distributor and Service Provider for Krendl Machines and Accessories

120 Claireville Drive, Etobicoke ON Canada M9W 5Y3 t:416-798-1235 info@climatizer.ca www.climatizer.ca



KRENDL

The Innovator in Insulation Equipment™

475

Scan to learn more about Krendl Machine

• POWER REQUIREMENT •

Double input, 15/15 amps each/120 volt/60 hz
International - Single input, 16 amp 230 volt/50 hz
CE/CSA/CUL/UL

• HOPPER CAPACITY •

14 cu. ft. (.39 m³)
Loading made easy with built in adaptable tray

• WEIGHT/DIMENSIONS •

360 lbs / 37" W x 31.5" D x 63" H
164 kg. / 94cm x 80cm x 160cm

• BLOWER/SIZE •

14 amp/2-stage (120 volt)
Blower System yields
140 CFM @ 3 1/2 PSI

• AIRLOCK •

12" x 10" diameter
(30.5 cm. x 25.4 cm. diameter)
3" (7.6 cm.) outlet



Electric Dashboard

- LED start & stop buttons
- Digital hourmeter
- Recessed power supply
- Digital voltmeter
- Variable blower speed control



Dual Agitators

Designed for Constant Material Flow



Clear Acrylic Safety Guard

Allows for easy Inspection