

425 Machine

ANY JOB. ANY SIZE. ANY PLACE.



The 425 is a proven leader in the do-it-yourself rental market. Designed for low maintenance, rugged performance, and portability. Capable of blowing all major brands of cellulose and fiberglass to the manufacturer's specifications.

- Lightweight
- Larger hopper capacity
- Durable powder coat finish base. Molded polyethylene hopper.

Two Options:
8amp or 14amp / 2 stage blower



**Proud Distributor and
Service Provider for Krendl
Machines & Accessories**

120 Claireville Drive
Etobicoke, ON M9W5W3
416-798-1235
climatizer.ca | info@climatizer.ca

AMERICAN MADE.

Backed by a manufacturer's 2-YEAR WARRANTY



The Innovator in Insulation Equipment

65 Years of American Ingenuity



Electric Panel
LED start button
Audible alarm
Motor reset
Fuse Protection



Dual Agitators
Designed for constant
material flow

POWER REQUIREMENT

Single input, 15 amp / 120V / 60Hz CSA/CUL/UL
Double input, 15/15amps each / 120V / 60Hz CSA/CUL/UL

HOPPER CAPACITY

7 cu.ft. (.20m³)

WEIGHT/DIMENSIONS

220lbs / 34"W x 25"D x 44" H
100kg. / 86cm x 64cm x 112cm

MATERIAL PRODUCTION RATE

Single 8amp blower

Cellulose
1100 (499)*

Fiberglass
200 (91)*

Single 14amp blower

Cellulose
1400 (634)*

Fiberglass
480 (217)*

*Lbs/hr (kg/hr) rating with 100 ft. (30.5m)
of 2 1/2" (6.4cm) hose at 10ft (3.1m) elevation.

BLOWER SIZE

8 amp / 2-Stage (120V)
Blower system yields 104CFM @ 2 PSI or
14 amp / 2-Stage (120V)
Blower system yields 140CFM @ 3.5 PSI

AIRLOCK

14" x 8" diameter
35.6cm x 20.3cm diameter
2.5"(6.4cm) Outlet

ACCESSORIES

Machine includes corded remote
Optional accessories sold separately

425 PACKAGE

Part Numbers	Description	QTY
425-B	425 Machine	1
H318	2 1/2" x 50' Hose	2
339A	2 1/2"-3" Clamps	3
379	2 1/2" Connector	1
EXTCORD-B	100' Extension Cords	2

OTHER OPTIONAL ACCESSORIES

Part Numbers	Description	QTY
328	36" Hose Reel	1
425MK	425 Maintenance Kit	1

ADDITIONAL ACCESSORY OPTIONS AVAILABLE UPON REQUEST

Note: Manufacturer's product brand, density and variable blowing conditions will affect production rate.